


**NOTE:**

ORDER ALL RedHeader PRO™ HEADERS  
1/2" LESS THAN ROUGH OPENING WIDTH  
TO FIT INSIDE HDSC HEADER BRACKETS.



CRIPPLE STUDS  
ABOVE OPENING

ATTACH TRACK TO  
HEADER STUD USING:  
(2) #10-16 SCREWS  
@ 24" O.C.

RedHeader PRO HEADER  
BRACKET. MEMBER SIZE AS  
REQ'D PER DESIGN. WITH (4)  
#10-16 SCREWS TO HEAD AND  
(4) #10-16 SCREWS TO JAMB

NOTE:

362 = 3-1/2" LONG  
400 = 3-7/8" LONG  
600 = 5-7/8" LONG  
800 = 7-7/8" LONG  
306 = 3-1/16" DEEP  
356 = 3-9/16" DEEP  
MILS: -33, -68, -97

RedHeader PRO. MEMBER  
SIZE AS REQ'D PER  
DESIGN.

(1) #10-16 SCREW  
TYP. EACH FLANGE

FULL HEIGHT RedHeader PRO  
JAMB STUD.  
MEMBER SIZE AS REQ'D  
PER DESIGN.

**BAILEY**®  
METAL PRODUCTS LIMITED

## RedHeader PRO™ CONNECTION

CURTAIN WALL 3" or 3-1/2" FLANGE HEADER USING:  
(1)HEADER STUD w/(1)TRACK

This detail library is intended to provide general framing details only and does not replace the judgments and designs of a qualified architect and/or engineer. The details are provided as a starting tool to assist the user in creating and detailing cold-formed steel framing construction details.

Each detail including accompanying text must be thoroughly evaluated and approved by a qualified architect or engineer.

© Copyright 2017 ClarkDietrich Building Systems For more information visit [www.bmp-group.com](http://www.bmp-group.com) or call (905) 738-9267